


# Micro Quick Connect Couplings

## single shut-off Series ESMC

**DN2.7**



Plug Profile (original size)

### Plugs with male thread

Thread connection	L	SW	L1	L2	Weight	Type No.
M 5 m	18	7	5	10	3	ESMC 5 NA
G 1/8 m	20	11	7	10	6	ESMC 18 NA

### Plugs with female thread

Thread connection	L	SW	L1	L2	Weight	Type No.
M 5 f	17	7	5	10	3	ESMC 5 NI
G 1/8 f	19	12	7	10	6	ESMC 18 NI

### Plugs with hose barb

Hose connection	L	D	L1	L2	Weight	Type No.
Hose i.D. 3	24	7	13	10	2	ESMC 3 S
Hose i.D. 4	24	7	13	10	3	ESMC 4 S
Hose i.D. 5	24	9	13	10	3	ESMC 5 S

For hose clips type ZOS (© page 314) or type HS (© page 315)

### Plugs with squeeze nut

Hose connection	L	SW	L1	Weight	Type No.
Hose 3x4	25	8	10	12	ESMC 34 SQ
Hose 3x5	25	8	10	12	ESMC 3 SQ
Hose 4x6	25	8	10	12	ESMC 4 SQ

### Plugs with squeeze nut and bulkhead screwing

Hose connection	L	SW	L1	L2	SW1	G	Weight	Type No.
Hose 3x4	38	12	17	10	11	M 7x0.5 m	23	ESMC 34 SQSV
Hose 3x5	38	12	17	10	11	M 7x0.5 m	23	ESMC 35 SQSV
Hose 4x6	38	12	17	10	12	M 8x0.5 m	23	ESMC 4 SQSV

### Plugs with hose barb and bulkhead screwing

Hose connection	L	SW	L1	L2	L3	SW1	G	Weight	Type No.
Hose i.D. 3	45	12	13	17	10	11	M 7x0.5 m	21	ESMC 3 SSV
Hose i.D. 4	45	12	13	17	10	11	M 7x0.5 m	21	ESMC 4 SSV
Hose i.D. 5	45	12	13	17	10	12	M 8x0.5 m	21	ESMC 5 SSV

Special versions and versions in brass plain on request.

