

Claw Couplings with Bore for Safety-Clips

- Robust couplings of malleable iron, zinc-plated and yellow passivated (free of chrome VI)
- 100 % couple-test and sight control
- With oil-resistant rubber ring GOER, on request with steam-resistant rubber ring GDOR (up to 200°C) against surcharge
- To be secured against accidental opening through safety-clips DIN 11024
- **Universal coupling, mainly used worldwide in mining or tunneling**

Materials

- Claw, connector: Malleable iron zinc-plated and yellow passivated (free of chrome VI)
- O-rings: Buna N

Max. Working Pressure	Temperature	Thread	Claw Distance	Media	
PN 10 bar	-40°C – +95°C	ISO 228, ANSI/ASME B 1.20,1	42 mm	Compressed air	10

Hose Claw Couplings with safety collar

Hose connection	L	B	L1	Passage	Weight	Type No.
Hose i.D. 13	74	63	40	8,5	167	SKSS 13
Hose i.D. 19	75	63	40	15	196	SKSS 19
Hose i.D. 25	75	63	40	19	222	SKSS 25

For hose clamps DIN 20039 B, type SK (☺ page 313), safe hose assembly

Female Claw Couplings

Thread connection	L	SW	B	L1	Passage	Weight	Type No.
G 1/2 f	37	27	63	14	18,5	141	KISS 12
G 3/4 f	39	32	63	14,5	20	145	KISS 34
G 1 f	41	41	63	18	20	182	KISS 10
NPT 1 f	41	41	63	18	20	180	KISS 10 NPT


NEW!

Male Claw Couplings


Thread connection	L	SW	B	L1	Passage	Weight	Type No.
G 1/2 m	49	27	63	14	13	170	KASS 12
G 3/4 m	49	32	63	15	17	182	KASS 34
G 1 m	53	39	63	15,5	20	199	KASS 10

Easy male thread sealing with PVC-Packing rings type HPD (☺ page 167)

Original Rubber Rings

Resistance	L	D	D1	Material	Temp.°C	Media	Colour	Shore A		Weight	Type No.
Oil	11	34	20	Buna N	-40 – +95	Compr.air	black	65°	100	6	GOER
Steam	10	33	20	TFEP	-40 – +200	Steam	red	65°	10	6	GDOR

Universal Safety-Clips DIN 11024

L	B	D	Material		Weight	Type No.
27	63	3	Steel zinc-plated	50	10	USC-1

